MATERIAL SAFETY DATA SHEET COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION								
Product Name: Air Tool Cleaner and Lubricant						HMIS Rating (Based on Aerosol Conc.):		
Product Number:	239		Date Prepared:	6/8/2009		0-Minimal 1-Slight 2-Moderate		
Product Type:	AEROSOL		Information Dhanay	(054) 074 5440		3-Serious 4-Extrem HEALTH:		
Formula: Supplier's Name:	Proprietary Terand Industries, Inc.		Information Phone:			FLAMMABILITY:		1 3
Supplier's Address: P.O. Box 667770, Pompano Beach, FL 33066		EL 22066	Emergency Phone: (800) 535-5053			PHYSICAL HAZARD:		0
DOT Ship Description: Consumer Commodity, ORM-D					Personal Protection		B	
DOT Ship Description.	Consumer Commodity, Chim-D							D
SECTION II - INGREDIENTS								
CHEMICAL NAME		CAS #	<u>%WT</u>	313/Chem	<u>Skin</u>	Carcinogen	PEL	TLV-TWA
Naphtha (Petroleum), L	ight Aliphatic	64742-89-8	30 - 40	NO	NO	NO	100 ppm	100 ppm
Isoparaffinic Hydrocarb	•	64742-66-8	10 - 20	NO	NO	NO	N/E	281 ppm*
Mineral Oil		8042-47-5	10 - 20	NO	NO	NO	5 mg/m3	5 mg/m3
Naphtha (Petroleum), Hydrotreated Light		64742-49-0	1 - 10	NO	NO	NO	500 ppm	346 ppm*
Ethanol	ija oli oaloa Ligin	64-17-5	1 - 10	NO	NO	NO	1000 ppm	1000 ppm
2010.00		00					rece pp	i ooo ppiii
Liquefied Petroleum Ga	as	68476-86-8	15 - 25	NO	NO	NO	1000 ppm	1000 ppm
*Manufacturer's Recommended Exposure Limit (TWA)								
SECTION III · PHYSICAL DATA								
Aerosol Concentrate:								
Boiling Point:	185 ℉		Specific Gravity (H20	D=1)@70°F:	0.779			
pH:	N/A		Solubility In Water:					
Appearance/Odor:	Red liquid with solvent odor		Vapor Density(Air=1)	:	>1			
Total Contents:								
Total VOC %:	81.62%		Vapor Pressure (can	; psig @72°F):	50 psig			
SECTION IV · FIRE AND EXPLOSION DATA								
Flash Point (Conc.): 40° F (TCC) Flammability (as per CSMA Flame Projection Test): Extremely-Flammable Spra								nmable Spray
Extinguishing Media: Foam, CO2, Dry Media								
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing. Unusual Fire and Explosion Hazards: Exposure to temperature above 120°F may cause bursting.								
SECTION V · REACTIVITY DATA								
Stability: Material Stable.				Hazardous Polyn	nerization:	Will not Occur.		
Incompatibility: Avoid contact with strong oxidizing agents.								
Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide.								
SECTION VI - STORAGE AND HANDLING								
KEEP OUT OF REACH OF CHILDREN.			NFPA Code 30B Rating:			Level 3 Aerosol.		
For Industrial and Institutional use only.								
Store in a cool, dry area away from heat or open flame.								
Do not store at temperatures above 120° F.								
SECTION VIL HEALTH AND FIRST AID								
PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:								
Eyes: May cause irritation accompanied by stinging, tearing, redness, and swelling.								
Evice Enclosed a match accompanies by aniging, realings, editions, and organized aviating akin conditions								

Skin: Frequent or prolonged contact may cause irritation and possibly dermatitis. May aggravate existing skin conditions.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the respiratory tract, dizziness, nausea, low

blood pressure, pulmonary edema, kidney damage, and other central nervous system effects, including unconsciousness and death. Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion of large amounts may cause mild, reversible liver effects. Aspiration of material into the lungs can cause pulmonary injury.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII - SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep air concentrations of ingredients listed in Section II below established limits.

Protective Gloves: Use chemical resistant gloves if hand contact will be made.

Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals...

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.