



SUPER DRY MOLY

LUBE & COAT NC



MEETS MIL-A-907D

Super Dry Moly Lube & Coat NC is a superior, long-lasting dry lubricant that withstands high temperatures and pressures. Repels dust and dirt and is resistant to water, alkalies and most acids. Prevents corrosion, seizing, wear, binding, squeaking and scraping. Withstands temperature ranges from -78°C to +565°C (-110°F to +1050°F). Resists pressures up to 100,000 psi. Contains pure Molybdenum Disulfide micro-particles which burnish themselves into metal surfaces and provide a bonded dry lubricating film.

INDUSTRIAL APPLICATIONS: Oil Drilling Equipment, Foundries, Automotive Plants, Vehicle Maintenance, Sewing Trades, Paper and Corrugated Converting, Chemical Plants, Woodworking, Marine, Agricultural & Military Equipment, Road Equipment, Aircraft Maintenance, Steel Mills and Mining Operations. Lubricates construction and other heavy equipment. May be applied wherever petroleum or synthetic lubricants are not suitable (except oxygen systems).

DIRECTIONS: Shake can vigorously. Surface must be clean and dry prior to application. Spray from a distance of 8 to 10 inches. Apply a thin, uniform coating. Allow to set approximately 3 to 5 minutes before applying second coat. After each use, invert can, use a short spray to clear button.

SUPER DRY MOLY LUBE & COAT NC

DANGER: Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international regulations.

FIRST AID: IF SWALLOWED: Immediately call a poison center/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF EXPOSED OR CONCERNED: Get medical advice/attention.

CONTAINS (CAS No.): Acetone (67-64-1), Butane (106-97-8), Propane (74-98-6), Aliphatic Petroleum Solvent (Mixture), Magnesium Silicate (14807-96-6), n-Heptane (142-82-5), Toluene (108-88-3), Cyclohexane (110-82-7), Methyl Ethyl Ketoxime (96-29-7) and n-Hexane (110-54-3).

Distributed by:

Golden West Industrial Supply
2180 Agate Court • Simi Valley, CA 93065
800-521-2601 • www.greenskeeper.com
www.gwisupply.com



KEEP OUT OF THE REACH OF CHILDREN

Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Warning: This product contains a chemical(s) known to the state of California to cause birth defects or other reproductive harm.

HMIS® RATING: Health, 2; Flammability, 4; Physical Hazard, 0; Personal Protection, X.

See Safety Data Sheet for complete safety information.

CONTAINS NO OZONE DEPLETING CHEMICALS!

24 HOUR MEDICAL EMERGENCY: 1-866-836-8855

MADE IN THE U.S.A.



Golden West Industrial Supply

SUPER DRY MOLY

LUBE & COAT NC



ANTI-FRICTION • ANTI-SEIZE
NON-CORROSIVE • WATERPROOF

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 12 OZ / 340 g