SAFETY DATA SHEET

1. Identification

Product number	100008842
Product identifier	19 OZ CLEAR VISION LB 12PK
Revision date	10-01-2014
Company information	GOLDEN WEST INDUSTRIAL SUPPLY 2180 AGATE COURT SIMI VALLEY, CA 93065 United States
Company phone	General Assistance 805-522-1000
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	02
Supersedes date	09-24-2014
Recommended use	Glass Cleaner
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Specific target organ toxicity, single exposure	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Causes damage to organs.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.
Response	If exposed: Call a poison center/doctor. Specific treatment (see this label).
Storage	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Not available.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	2.5 - 10
Methanol		67-56-1	2.5 - 10
Ethyl Alcohol		64-17-5	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below report	rtable levels		90 - 100

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	If symptoms develop move victim to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Skin contact	Call a physician or Poison Control Center immediately.
Eye contact	Call a physician or Poison Control Center immediately.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Immediate medical attention is required. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. If possible, turn leaking containers so that gas escapes rather than liquid. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.
Environmental precautions	Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Will ignite if exposed to intensive heat or open air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Do not get this material in contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 1 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep container dry. Refrigeration recommended. Keep away from food, drink and animal feedingstuffs. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре)	V	alue	
Ethyl Alcohol (CAS 64-17-	5) PEL			900 mg/m3	
				000 ppm	
Methanol (CAS 67-56-1)	PEL			60 mg/m3	
				00 ppm	
Propane (CAS 74-98-6)	PEL			300 mg/m3	
			10	000 ppm	
US. ACGIH Threshold Li					
Components	Туре		V	alue	
Butane (CAS 106-97-8)	STEL	_	1()00 ppm	
Ethyl Alcohol (CAS 64-17-			10	000 ppm	
Methanol (CAS 67-56-1)	STEL	-	2	50 ppm	
	TWA		20	00 ppm	
US. NIOSH: Pocket Guid	e to Chemical Hazards				
Components	Туре	•	V	alue	
Butane (CAS 106-97-8)	TWA		19	900 mg/m3	
			80	00 ppm	
Ethyl Alcohol (CAS 64-17-	5) TWA		19	900 mg/m3	
				000 ppm	
Methanol (CAS 67-56-1)	STEL	_		25 mg/m3	
				50 ppm	
	TWA	L.		60 mg/m3	
				00 ppm	
Propane (CAS 74-98-6)	TWA			300 mg/m3	
			10	000 ppm	
ological limit values					
ACGIH Biological Expos					
Components	Value	Determinant	Specimen	Sampling Time	
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*	
* - For sampling details, pl	ease see the source doci	ument.			
posure guidelines					
US - California OELs: Sk	in designation				
Methanol (CAS 67-56	•	Can b	e absorbed thro	uah the skin.	
US - Minnesota Haz Subs: Skin designation applies					
Methanol (CAS 67-56	•		lesignation appli	es.	

US - Tennesse OELs: Skin de	esignation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.	
US ACGIH Threshold Limit V	alues: Skin designation	
Methanol (CAS 67-56-1) Can be absorbed through the skin.		
US NIOSH Pocket Guide to C	hemical Hazards: Skin designation	
Methanol (CAS 67-56-1)	Can be absorbed through the skin.	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
Individual protection measures,	such as personal protective equipment	
Eye/face protection	Wear tight-fitting goggles or face shield.	
Hand protection	Wear appropriate chemical resistant gloves.	
Skin protection		
Other	Use of an impervious apron is recommended.	
Skin protection		
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	Do not get in eyes. When using do not smoke. Do not get this material in contact with skin. Avoid contact with skin. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	23.01 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Product name: 19 OZ CLEAR VISIO	
D 1 <i>i i i i i i i i</i>	

Viscosity Other information	Not available.
Specific gravity	0.968 estimated
10. Stability and reactivity	/
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of ignition.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Exposure to air. Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Oxygen. Do not mix with other chemicals.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause damage to organs by inhalation. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
	• · ·

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
19 OZ CLEAR VISION LB	12PK (CAS Mixture)	
Acute		
Dermal		
LD50	Guinea pig	30568.8457 ml/kg, 24 Hours estimated
		970.2286 ml/kg, 4 Days estimated
	Rabbit	49755.8828 mg/kg estimated
		2824.3066 ml/kg, 24 Hours estimated
	Rat	22114 mg/kg
Inhalation		
LC100	Cat	1800.036 % estimated
LC50	Cat	2996.8423 mg/l, 4.5 Hours estimated
		1532.6316 mg/l, 6 Hours estimated
	Mouse	24740.4941 mg/l, 120 Minutes estimated
		3427.9429 mg/l, 4 Hours estimated
		3340.0469 mg/l, 24 Hours estimated
		2787.0176 mg/l, 134 Minutes estimated
		1040.0208 %, 120 Minutes estimated
		320.0064 mm/l, 2 Hours estimated
	Rabbit	53163.2109 ppm, 7 Hours estimated
	Rat	48639.8242 ppm, 4 Hours estimated
		4498.2456 mg/l, 4 Hours estimated
		3073.6843 mg/l, 6 Hours estimated
		204 mg/l/4h

Product	Species	Test Results
Oral		
LD100	Rabbit	92371.0781 mg/kg estimated
LD50	Dog	92371.0781 mg/kg estimated
	Rat	25019.3789 mg/kg estimated
Other		
LD50	Mouse	86843.7656 mg/kg estimated
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation LC50	Mouro	1227 mg/L 120 Minutos
LC30	Mouse	1237 mg/l, 120 Minutes
	_	52 %, 120 Minutes
	Rat	1355 mg/l
Ethyl Alcohol (CAS 64-17-5)		
Acute		
Inhalation	0-1	
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Mouse	10500 ml/kg
	Rat	7800 ml/kg
		7060 mg/kg
Other		
LD50	Mouse	6000 mg/kg
	Rat	4070 mg/kg
Methanol (CAS 67-56-1)		
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
	Kat	82.1 mg/l, 6 Hours
Oral		oz. r mgn, o riours
<i>Oral</i> LD50	Monkey	6000 mg/kg
2000	Rat	1187 - 2769 mg/kg
Other	mai	1107 - 2709 Highty
<i>Other</i> LD50	Mouse	6000 mg/kg
	WOUSE	oooo mg/kg
Propane (CAS 74-98-6)		
Propane (CAS 74-98-6) Acute		
Propane (CAS 74-98-6)	Mouse	1237 mg/l, 120 Minutes

Components	Species	Test Results
	Rat	1355 mg/l
		658 mg/l/4h
* Estimates for product may I	be based on additional component data no	ot shown.
Skin corrosion/irritation	Prolonged skin contact may cause tem	porary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause ten	nporary irritation.
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause s	kin sensitization.
Germ cell mutagenicity	No data available to indicate product or mutagenic or genotoxic.	any components present at greater than 0.1% are
Carcinogenicity	Risk of cancer cannot be excluded with	prolonged exposure.
OSHA Specifically Regulate Not listed.	ed Substances (29 CFR 1910.1001-1050)
Reproductive toxicity	This product is not expected to cause re	eproductive or developmental effects.
Specific target organ toxicity - single exposure	Causes damage to organs.	
Specific target organ toxicity - repeated exposure	Respiratory system. Skin. Central nervo	ous system. Eyes. Gastrointestinal tract.
Aspiration hazard	Not likely, due to the form of the produc	st.
Chronic effects	Prolonged inhalation may be harmful. F	Prolonged exposure may cause chronic effects.
Further information	Danger of very serious irreversible effe	cts.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
19 OZ CLEAR VISION LB	12PK (CAS Mix	ture)	
Aquatic			
Algae	IC50	Algae	5714 mg/L, 72 Hours
Fish	LC50	Fish	57589 mg/L, 96 Hours
Components		Species	Test Results
Ethyl Alcohol (CAS 64-17-5	5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100.1 mg/l, 96 hours
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-	octanol / water (log Kow)	
Butane		2.89
Ethyl Alcohol		-0.31
Methanol		-0.77
Propane		2.36
Mobility in soil	No data available.	

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
US RCRA Hazardous Waste	U List: Reference	
Methanol (CAS 67-56-1)	U154	

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN1950
Aerosols, flammable, (each not exceeding 1 L capacity)
2.1
-
2.1
Not applicable.
Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
N82
306
None
None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

	~	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo aircraft	Allowed.
	Cargo aircraft only	Allowed.
	Packaging Exceptions	LTD QTY
IMI	DG	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1

Packing groupNot applicable.Environmental hazardsNo.Marine pollutantNo.EmSF-D, S-USpecial precautions for userRead safety instructions, SDS and emergency procedures before handling. Read safety
instructions, SDS and emergency procedures before handling.Packaging ExceptionsLTD QTYTransport in bulk according to
Annex II of MARPOL 73/78 andNot applicable.

DOT FLAMMABLE GAS 2 IATA; IMDG

15. Regulatory information

JS federal regulations	This product is a "Hazardou Standard, 29 CFR 1910.120 All components are on the U	00.	ned by the OSHA Hazard Communication ntory List.
TSCA Section 12(b) Export	Notification (40 CFR 707, Su	ıbpt. D)	
Not regulated.			
CERCLA Hazardous Substa	ance List (40 CFR 302.4)		
Methanol (CAS 67-56-1)		Listed.	
SARA 304 Emergency relea	se notification		
Not regulated.			
OSHA Specifically Regulate	ed Substances (29 CFR 1910	.1001-1050)	
Not listed.			
Superfund Amendments and Re	authorization Act of 1986 (S	SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazar	dous substance		
Not listed.			
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting)			
Chemical name		CAS number	% by wt.
Methanol		67-56-1	2.5 - 10
1,4-Dioxane		123-91-1	0.01 - 0.1

			% by wt.	
Safrole		94-59-7	0.01 - 0.1	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutan	ts (HAPs) List		
Methanol (CAS 67-56-1) Clean Air Act (CAA) Section	112(r) Accidental Release P	revention (40 CFR 6	68.130)	
Butane (CAS 106-97-8) Propane (CAS 74-98-6)				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations	WARNING: This product cor defects or other reproductive		wn to the State of Califo	ornia to cause birth
US. Massachusetts RTM	C - Substance List			
Butane (CAS 106-97 Ethyl Alcohol (CAS 6 Methanol (CAS 67-50 Propane (CAS 74-98 US. Pennsylvania Work Butane (CAS 106-97 Ethyl Alcohol (CAS 66 Methanol (CAS 67-50 Propane (CAS 74-98 US. Rhode Island RTK Butane (CAS 106-97 Methanol (CAS 67-50 Propane (CAS 74-98 US. California Proposition 6	4-17-5) 5-1) -6) and Community Right-to-Kr -8) 4-17-5) 5-1) -6) er and Community Right-to-I -8) 4-17-5) 5-1) -6) -8) -8) 5-1) -6)	Know Law	a to cause cancer and b	irth defects or other
·	ion 65 - CRT: Listed date/Ca	rcinogenic substan	60	
1,4-Dioxane (CAS 12 Safrole (CAS 94-59-	23-91-1)	Listed: January 1, Listed: January 1,	, 1988	
Methanol (CAS 67-5		Listed: March 16,	2012	
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Chen	nical Substances (AIC	CS)	No
Canada	Domestic Substances List (E	DSL)		Yes
Canada	Non-Domestic Substances L	ist (NDSL)		No
China	Inventory of Existing Chemical Substances in China (IECSC)		No	
Europe	European Inventory of Existi Substances (EINECS)	ng Commercial Chen	nical	No
Europe	European List of Notified Ch	emical Substances (E	ELINCS)	No
Japan	Inventory of Existing and Ne	w Chemical Substand	ces (ENCS)	No
Korea	Existing Chemicals List (ECL	_)		No
New Zealand	New Zealand Inventory			No
Philippines	Philippine Inventory of Chem (PICCS)	nicals and Chemical S	Substances	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	09-24-2014
Revision date	10-01-2014
Version #	02
Disclaimer	We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Product and Company Identification