

1. IDENTIFICATION

Product Name: SPOTLESS™
Product Type and Use: Cleaner / Degreaser
Manufactured for: GOLDEN WEST Industrial Supply
2180 Agate Ct., Simi Valley, CA 93065
Contact: Telephone: 1-805-522-1000 or 1-800-521-2601
Product Info: Telephone: 972-271-7361
Emergency Telephone: CHEMTREC® USA (800) 424-9300
Outside US (703) 927-3887

2. HAZARDS IDENTIFICATION

Hazard Classification

Health Hazard(s)

Skin Corrosion/Irritation Category 1C
Eye Irritation Category 1
Acute Toxicity - Inhalation Category 4
Acute Toxicity - Oral Category 4
STOT RE Category 3

Physical Hazard(s)

Corrosive to metals Category 1

Hazard(s) not otherwise classified

None

Labeling

Signal Word: DANGER
Pictograms: Corrosion, Health Hazard

Statements of Hazard

Hazard Statements

Causes severe skin burns and eye damage
Harmful if inhaled or swallowed
May cause respiratory irritation
May be corrosive to metals

Precautionary Statements

Wear protective gloves, eye and face protection. Do not breathe vapors or mist. Use only outdoors or in a well-ventilated area. Take off contaminated clothing and wash it before reuse. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Store locked up in a well ventilated place. Keep only in original container. Absorb spillage to prevent material damage. Store in corrosive resistant container with resistant inner liner. Dispose of contents and container in accordance with applicable regulations.
If on skin: Rinse skin with water/shower. Immediately call a poison center or doctor.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor.
If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Percent by Wt.
Ethylene Glycol butyl ether	111-76-2	1-5*
Sodium Metasilicate	6834-92-0	1-5*
Ethoxylated alcohol phosphate	Trade Secret	1-5*

* Exact percentage of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice: Causes skin and eye damage. May be absorbed through the skin; avoid contact. Do not swallow. Avoid breathing vapor or mist. Use with adequate ventilation. Keep container closed.

Inhalation: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor.

Skin Contact: Remove contaminated clothing. Flush skin with plenty of water. Remove contaminated clothing and wash before reuse. Immediately call a poison center or doctor.

Eye Contact: Immediately flush cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

Ingestion: Do not give anything by mouth to an unconscious person. Do not induce vomiting unless advised to do so by a doctor or poison control center. Rinse mouth. Immediately call a poison center or doctor.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Product does not support combustion. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Suitable: Carbon Dioxide, Dry Chemical, and Foam

Unsuitable: Alcohol, Alcohol based solutions

Fire Fighting Procedures: As in any fire, wear self-contained breathing apparatus, pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool fire-exposed containers with water spray.

Unusual Fire and Explosion Hazards: Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc.

Hazardous Combustion/ Decomposition Products: Oxides of carbon, phosphorous and nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions / Protective Equipment / Emergency Procedures: Use caution as spills may be slippery. Ensure adequate ventilation. Use personal protective equipment.

Methods and materials for containment and cleaning up: Small spills of one gallon or less may be flushed with plenty of water to sanitary sewer system (If permitted by local sewer regulations). Dike and contain large spills with inert absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer liquid to plastic containers. Do not store or dispense into metal containers; especially aluminum. Use clean non-sparking tools to collect absorbed material and transfer to a properly labeled container for recovery or disposal according to local / national regulations.

7. HANDLING AND STORAGE

HANDLING

Precautions for Safe Handling: Avoid skin and eye contact. Use with adequate ventilation. The headspace of unopened containers and empty containers may contain trace amounts of ethylene oxide. Avoid breathing vapor and mist. Follow all SDS/label precautions.

STORAGE

Conditions to avoid: Store in a cool, dry, well-ventilated place in the original container. Separate from acids, reactive metals, and ammonium salts. Do not store or transfer in aluminum, fiberglass, copper, brass, zinc or galvanized containers. Keep container tightly closed when not in use. Freezing will affect the physical condition but will not damage the material. Thaw and mix before using.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

Component	ACGIH		OSHA		STEL ppm	STEL mg/m3
	TLV ppm	TLV mg/m3	PEL ppm	PEL mg/m3		
Ethylene Glycol butyl ether	20 (Skin)	-	50	240	-	-
Sodium Metasilicate	N/E	2**	N/E	N/E	N/E	N/E
Ethoxylated alcohol phosphate	N/E	N/E	N/E	N/E	N/E	N/E
Ethylene Oxide	1	-	-	-	-	9

**Manufacturers recommended exposure limit

Engineering Controls: Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

Personal Protection

Respiratory Protection: None required under normal use conditions. In case of insufficient ventilation, wear a suitable NIOSH approved air purifying respirator.

Hand / Skin Protection: Wear impermeable gloves such as neoprene or nitrile rubber gloves. Gauntlets and apron may be worn depending on the extent of exposure.

Eye / Face Protection: Face shield with safety glasses with side-shields.

General Hygiene Measures: Avoid contact. Always wash hands and face before eating, drinking or smoking. Remove and wash contaminated clothing before re-use. An eyewash station and washing facilities should be readily accessible to the area of use. See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Transparent	Autoignition Temperature:	Not applicable
Physical State:	Non-viscous liquid	Percent Volatile by volume:	92
Odor:	Pleasant	Vapor Density (Air=1):	1
Color:	Light Blue	Evaporation Rate (BuAc= 1):	<1
Viscosity, cSt @ 40°C:	Not established	Vapor Pressure, mmHg @23°C:	21.1
cSt @ 100°C:	Not established	Solubility in water:	Complete
pH:	12.3-13	Octanol/Water Partition:	Not established
Boiling Point/ Range:	>200°F / 93°C	VOC Content (%):	5
Melting Point:	>32°F / 0°C	Specific Gravity @15.6°C:	1.02
Flash Point:	Non-flammable	Pour Point:	>32°F / 0°C
Method:	Not applicable	Percent non-volatile by Volume:	8
Lower Explosive Limit, vol %:	Hydrogen 4 %	Dielectric Strength:	Not applicable
Upper Explosive Limit, vol %:	Hydrogen 75 %		

10. STABILITY AND REACTIVITY

Stability: Stable at ambient temperatures.

Conditions to Avoid: None known

Hazardous Polymerization: Will not occur.

Materials to Avoid: Aluminum and other reactive metals, glass, oxidizing agents, acids. May react with ammonium salt solutions resulting in evolution of ammonia gas. Carbon monoxide gas may be produced on contact with reducing sugars.

11. TOXICOLOGICAL INFORMATION

Product Information: Not established

Ingredient Information

Acute Toxicity

2-Butoxyethanol: LD50 Oral 470 mg/kg (Rat), LD50 Dermal 220 mg/kg (Rabbit), LC50 Inhalation 450 ppm (Rat) 4 h

Sodium metasilicate: LD50 Oral 600 mg/kg (Rat)

Ethoxylated alcohol phosphate: LD50 Oral 15,300 mg/kg (Rat) estimated, LD50 Dermal 27,400 mg/kg (Rabbit) estimated

Acute Effects

Signs and Symptoms of Overexposure: Skin and serious eye irritation, Coughing/Sneezing

Inhalation: Vapor and mist may cause respiratory irritation with nasal discomfort and discharge, coughing and sneezing.

Skin Contact: May cause redness, pain and burns. May be absorbed through skin in harmful amounts.

Eye Contact: May cause tearing, redness, pain, swelling of the conjunctiva and burns. May cause blindness.

Ingestion: May cause pain, nausea, vomiting and diarrhea.

Primary Route(s) of Exposure: Eyes, Skin, Inhalation

Primary Route(s) of Entry: Inhalation, Ingestion

Target Organs: Liver, kidneys, lymphatic system, skin, blood, eyes, CNS, respiratory system

Chronic Effects

2-Butoxyethanol Target Organ Effects: liver, kidneys, lymphatic system, skin, blood, eyes, CNS, respiratory system

Carcinogenicity

2-Butoxyethanol: ACGIH A3 IARC Group 3

Medical Conditions Aggravated by Exposure: May aggravate existing skin, eye and respiratory conditions including asthma and dermatitis.

12. ECOLOGICAL INFORMATION

Product Data: Not established

Ingredient Data

2-Butoxyethanol: Toxicity to Fish LC50 = 1490 mg/L *Lepomis macrochirus* 96 h, Water Flea EC50 1698 - 1940 mg/L 24 h *Daphnia magna*, 1000 mg/L 48 h *Daphnia magna*

Sodium metasilicate: Toxicity to Fish LC50 = 210 mg/L *Brachydanio rerio* 96 h, Water Flea EC50 216 mg/L 96 h *Daphnia magna*

Elimination Information: 2-Butoxyethanol: log POW 0.81

13. DISPOSAL CONSIDERATIONS

Product: Dispose of in accordance with local regulations.

Container: Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

Road Transport

DOT Hazard Class: 8

Description: Corrosive liquid

UN-No.: 3266

Proper Shipping Name: Corrosive liquid, basic, inorganic, n.o.s. (Sodium metasilicate)

Sea Transport

IMDG/GGV See Class: 8

UN-No.: UN3266

Packing Group: III

Proper Shipping Name: Corrosive liquid, basic, inorganic, n.o.s. (Sodium metasilicate)

Air Transport

ICAO/IATA Class: 8

UN-No.: UN3266

Packing Group: III

Shipping Name: Corrosive liquid, basic, inorganic, n.o.s. (Sodium metasilicate)

15. REGULATORY INFORMATION

U.S. Federal Regulations

Toxic Substances Control Act (TSCA): All components are included on the Inventory

Superfund Amendments and Reauthorization Act (SARA) Title III:

Immediate Hazard	Delayed Hazard	Fire Hazard	Pressure Hazard	Reactivity Hazard
X	X	-	-	-

16. OTHER INFORMATION

Prepared by: GOLDEN WEST Industrial Supply, Technical Services Department

Revision Date: 7/23/2015

Supersedes Date: Not applicable

Revision Indicator: New OSHA 2012 SDS

National Fire Protection Association (704)

Health: 1 Flammability: 1 Reactivity: 0 Other: -

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damage incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical and application of such products is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the sole responsibility of the user to comply with all applicable Federal, State and Local Laws and Regulations. Any questions with regards to information contained herein should be referred to: U. S. Corrosion Technologies, LLC (972) 271-7361.